Omni-directional



Barcode Scanner XL-2000











- Two years warranty
- With CE, FCC certificates
- § 32 bit CPU, with 5 mil optical resolution
- Plug and play, no need any driver, easy operation
- Large scan window, good choice for supermarket
- 20 scan lines at a rate of 1500 scans per second



Light Source	Visible Laser Diode 650nm	Size	$L \times W \times H:152mm \times 78mm \times 152mm$
Scan Pattern	20 lines 5 fields of 4 parallel lines	Weight	610g
Scan speed	1500 scans/s	Material	ABS+PC
Print Contrast	30% @ UPC/EAN 100%	Laser Class	Meet the Grade I National Criteria for Laser Safety
Minimum Resolution	5mil@PCS90%	Voltage	5 Volts
Depth of Field	0-220mm for 0.33mm UPC/EAN100%	Static Current	250mA
Host System Interfaces	USB, RS232,Keyboard Wedge	EMC	CE& FCC DOC compliance
Visual Indicators	Two color LED (blue & red)	Operating Temperature	- 0°C to 45°C
Beeper Opperation	Programmable tone & volume	Storage Temperature	- 20°C to 60°C
Cable	Standard 2M straight	Humidity	5% to 85% relative humidity,non-condensing
Decoding Capability	UPC/EAN/JAN, UPC-A & UPC-E, EAN-8 & EAN-13, JAN-8 & JAN-13, ISBN/ISSN, Code 39 (with full ASCII), Codabar (NW7), Code 128 & EAN 128, Code 93, Interleaved 2 of 5 (ITF), Addendum 2 of 5, MSI/Plessy, Code 32 (Italian Pharmacode), RSS 14, RSS Limited, RSS Expanded, China post, Industry 2 of 5, Standard 2 of 5.		

