

# 1D Handheld Barcode Scanner XL-6200



- ⊙ Very comfortable operating sense.
- ⊙ Decode most popular 1D barcodes.
- ⊙ Quick and fluent reading performance.
- ⊙ Ready for all POS system and ideal for retail.
- ⊙ With IP54 waterproof and dustproof protection.



|                     |                                                                                                                            |                     |                                 |
|---------------------|----------------------------------------------------------------------------------------------------------------------------|---------------------|---------------------------------|
| Model Number        | XL-6200                                                                                                                    | Indicator           | Buzzer, Indicator               |
| CPU                 | 32 Bit ARM                                                                                                                 | Dimension           | L x W x H: 175mm x 73mm x 102mm |
| Light Source        | Visible Laser Diode 650nm                                                                                                  | Weight              | 239g                            |
| Scan pattern        | Single Scan                                                                                                                | Material            | ABS + PC                        |
| Scan Rate           | 300 times/second                                                                                                           | Operating Current   | 85mA                            |
| Scan Precision      | 3mil                                                                                                                       | Voltage             | DC 5V                           |
| Scan Width          | 30mm@scan window, 220mm@200mm                                                                                              | Static Current      | 36mA                            |
| Scan Depth of Field | 0-320mm (0.33mm pcs0.9)                                                                                                    | Laser Class         | Class 1                         |
| Scan Angle          | 30° & 65° & 55°                                                                                                            | EMC                 | CE & FCC DOC compliance         |
| Interface           | RS 232 & PS2 & USB(not interchangeable)                                                                                    | Operate Temperature | 0°C to 45°C                     |
| Print Contrast      | 10% UPC/EAN 100%                                                                                                           | Storage Temperature | - 20°C to 60°C                  |
| Decoding Capability | EAN-8/EAN-13/UPC-A/UPC-E/Code 39/Code 93/Code 128/EAN128/Codabar/Industial 2 of 5/<br>Interleave 2 of 5/Matrix 2 of 5/MSI. |                     |                                 |



**SUNLUX IOT Technology (Guangdong) Inc.**

Office Add: 4F,No.7 ,Kehui First Street ,Science Road,Science City,Guangzhou,China

Tel: +86-20-32053765 Fax: +86-20-82115390 Site: [www.xl-scan.com](http://www.xl-scan.com) E-mail: [sales@xl-scan.com](mailto:sales@xl-scan.com)