

# 2D Barcode Scanner



## XL-3500



- ⊙ Good solution for industrial using
- ⊙ Read inverse barcode symbology
- ⊙ Ergonomic, snappy and stylish design
- ⊙ Read all major 1D and 2D barcode symbologies
- ⊙ IP65 rating for a dustproof & waterproof functionality



Image Sensor	CMOS	Dimension	L × W × H:186mm × 66mm × 90mm
Image size	752 × 480 pixels	Weight	285g
Light Source	Red light,LED, 622nm±10nm	Material	ABS+PC
Precision	≥5mil	Voltage	DC 5V ± 10%
Depth of Scan Field	35-170mm(Code39,10mil),45-140mm(QR,10mil)	Current (Working)	400mA
Scensitivity	Roll:360° Skew:±55°, Pitch:±55°	Operate Temperature	- 20°C to 45°C
Support Interface	USB and RS232	Storage Temperature	- 40°C to 60°C
Print Contrast Signal	≥30%	Humidity	5% to 95%
Indicator	Buzzer, LED	Illumination	0 to 100000LUX
Scan Mode	Manual & Automatic	Certification	EC (EMC) Class B,Rohs,FCC
Decoding Capability	1D: EAN-8,EAN-13,UPC-A,UPC-E,Code39,Code93,Code128,EAN128, Codabar, Industrial 2of 5, Interleave 2of5, Matrix 2 of 5,MSI, Chinese postcode etc. 2D: PDF417,QR Code (Mode/2), DataMatrix(ECC200,ECC000,050,080,100,140),etc.		



**SUNLUX IOT Technology (Guangdong) Inc.**

Office Add: 4F,No.7 ,Kehui First Street ,Science Road,Science City,Guangzhou,China

Tel: +86-20-32053765 Fax: +86-20-82115390 Site: [www.xl-scan.com](http://www.xl-scan.com) E-mail: [sales@xl-scan.com](mailto:sales@xl-scan.com)