

Wireless Scanner

XL-9310



- ⊗ 1 base frame can support 99 scanners
- ⊗ Wireless induction charge without cable
- ⊗ IP54 standard and withstand 1.5M drops
- ⊗ With memory card inserted in scanner and can store 100000 EAN-13 barcode
- ⊗ One full charge support 100,000 times scanning
- ⊗ The communication distance on open places is 600m



Light Source	Visible Laser Diode 650nm	Size	L × W × H:170mm × 71mm × 98mm
Scan Pattern	Single Scan & Manual	Charge Mode	Wireless charging
Working Frequency	433 MHz ISM frequency	Weight	180g
Communication distance	Up to 600m at open places	Material	ABS+PC
Scan Precision	3mil(pcs0.9)	Voltage	2200 mAh/DC 12V
Scan Rate	300 times/scend	Operating Current	110mA/35mA
Scan Width	30mm@scan window,220mm@200m	EMC	CE & FCC DOC compliance
Depth of Scan Field	0-280mm(0.33mm pcs0.9)	IP Standard	IP54
Scan Angle	30° & 65° & 55°	Decoding Capability	all 1D barcode including GS1
Support Interface	RS232,PS2 and USB	Humidity	5% to 95% relative humidity
Print Contrast	30% UPC/EAN 100%	Shock	1.5M drops
Decoding Capability	EAN-8,EAN-13,UPC-A,UPC-E,Code 39,Code 93,Code 128,EAN 128,Codabar,Industrial 2 of 5, Industrial 2 of 5,Matrix 2 of 5,MSI,中国邮政码等。		



SUNLUX IOT Technology (Guangdong) Inc.

Office Add: 4F,No.7 ,Kehui First Street ,Science Road,Science City,Guangzhou,China

Tel: +86-20-32053765 Fax: +86-20-82115390 Site: www.xl-scan.com E-mail: sales@xl-scan.com