

Wireless Scanner



XL-9528



- ⊙ Large Capacity Battery 2200mAh
- ⊙ IP65 standard and Withstand 2M drops
- ⊙ Wireless induction charge without cable
- ⊙ 600M Communication distance on open places
- ⊙ Idea for warehouse and industrial environment use



Light Source	Visible Laser Diode 650m	Size	L × W × H:186mm ×66mm × 108mm
Scan Pattern	Single Scan & Manual	Charge Mode	Wireless charging
Working Frequency	433 MHz ISM frequency	Weight	180g
Communication distance	Up to 600m at open places	Material	ABS+PC
Scan Precision	3mil(pcs0.9)	Voltage	2200 mAh/DC 12V
Scan Rate	300 times/scend	Operating Current	130mA/35mA
Scan Width	30mm@scan window,220mm@200m	EMC	CE & FCC DOC compliance
Depth of Scan Field	0-350mm(UPC/EAN100%,pcs0.9,13mil)	IP Standard	IP65
Scan Angle	30° &65° & 55°	Decoding Capability	all 1D barcode including GS1
Support Interface	RS232,PS2 and USB	Humidity	5% to 95% relative humidity
Print Contrast	30% UPC/EAN 100%	Shock	2M drops
Decoding Capability	EAN-13/EAN-8/UPC-A/UPC-E/ ISSN/ISBN/Codabar/ Code 128(FNC1/FNC2/FNC3子集) /Code93/ITF-6/ITF-14/ Interleave 2 of 5/Industrial 2 of 5/standard 2 of 5/Matrix 2 of 5/GS1 Databar/Code 39/ Code 39 FULL ASCII/CODE11, MSI, PLESSEY等。		



SUNLUX IOT Technology (Guangdong) Inc.

Office Add: 4F,No.7 ,Kehui First Street ,Science Road,Science City,Guangzhou,China

Tel: +86-20-32053765 Fax: +86-20-82115390 Site: www.xl-scan.com E-mail: sales@xl-scan.com