

# Omni-directional Barcode Scanner



## XL-2200



- ⊙ 20 laser scan lines in 5 directions
- ⊙ Scan rate up to 1500 scans per second
- ⊙ Suit for USB, RS-232, USB-VCP interface port
- ⊙ Self-developed 32 bit decoder chip & hardware decode
- ⊙ Powerful performance on decode capability, can read GS1 code



Model Number	XL-2200	Size	L × W × H:105mm × 100mm × 156mm
Light Source	Visible Laser Diode 650nm	Weight	283g
Scan Pattern	20 lines 5 fields of 4 parallel lines	Material	ABS+PC
Scan speed	1500 scans/s & 75 scans/s	Laser Class	Meet the Grade I National Criteria for Laser Safety
Print Contrast	30% @ UPC/EAN 100%	Voltage	5 Volts
Minimum Resolution	4mil	Static Current	250mA
Depth of Field	0-220mm for 0.33mm UPC/EAN100%	Operating Temperature	- 0°C to 45°C
Host System Interfaces	USB, RS232,USB-VCP	Storage Temperature	- 20°C to 60°C
Visual Indicators	Two color LED (blue & red)	Humidity	5% to 85% relative humidity
Beeper Operation	Programmable tone & volume	Light Levels	Daylight,5000LUX
Cable	Standard 2M straight	Shock	Designed to 1.5m drops
Decoding Capability	UPC/EAN/JAN, UPC-A & UPC-E, EAN-8 & EAN-13, JAN-8 & JAN-13, ISBN/ISSN, Code 39 (with full ASCII), Codabar (NW7), Code 128 & EAN 128, Code 93, Interleaved 2 of 5 (ITF), Addendum 2 of 5, IATA Code, MSI/Plessey, Code 32 (Italian Pharmacode), RSS 14, RSS Limited, RSS Expanded		



**SUNLUX IOT Technology (Guangdong) Inc.**

Office Add: 4F,No.7 ,Kehui First Street ,Science Road,Science City,Guangzhou,China

Tel: +86-20-32053765 Fax: +86-20-82115390 Site: [www.xl-scan.com](http://www.xl-scan.com) E-mail: [sales@xl-scan.com](mailto:sales@xl-scan.com)