

Omni-directional Barcode Scanner



XL-2002



- ⊙ Two years warranty
- ⊙ With CE certificate
- ⊙ Firmware can be upgraded online
- ⊙ Suit for USB, RS-232, USB-VCP interface port
- ⊙ Suitable for supermarkets, pharmacies, retail stores
- ⊙ Powerful performance on decode capability, can read GS1 code



Light Source	Visible Laser Diode 650nm	Size	L × W × H:100mm × 100mm × 149mm
Scan Pattern	20 lines 5 fields of 4 parallel lines	Weight	314g
Scan Speed	1500 scans/s	Material	ABS+PC
Print Contrast	30% @ UPC/EAN 100%	Laser Class	Meet the Grade I National Criteria for Laser Safety
Minimum Resolution	4mil	Voltage	5 Volts
Depth of Field	0-220mm for 0.33mm UPC/EAN100%	Static Current	250mA
Host System Interfaces	USB, RS232,USB-VCP	EMC	CE DOC compliance
Visual Indicators	Two color LED (blue & red)	Operating Temperature	- 0°C to 45°C
Beeper Operation	Programmable tone & volume	Storage Temperature	- 20°C to 60°C
Cable	Standard 2M straight	Shock	Designed to 1.5m drops
Decoding Capability	UPC/EAN/JAN, UPC-A & UPC-E, EAN-8 & EAN-13, JAN-8 & JAN-13, ISBN/ISSN, Code 39 (with full ASCII), Codabar (NW7), Code 128 & EAN 128, Code 93, Interleaved 2 of 5 (ITF), Addendum 2 of 5, MSI/Plessey, Code 32 (Italian Pharmacode), RSS 14, RSS Limited, RSS Expanded, Industry 2 of 5, Standard 2 of 5.		



SUNLUX IOT Technology (Guangdong) Inc.

Office Add: 4F,No.7 ,Kehui First Street ,Science Road,Science City,Guangzhou,China

Tel: +86-20-32053765 Fax: +86-20-82115390 Site: www.xl-scan.com E-mail: sales@xl-scan.com