

# Wireless Scanner



## XL-9309



- ⊙300m communication distance
- ⊙Simple pairing by scanning one code
- ⊙1 base frame can support 99 scanners
- ⊙Ensure 100% succesful data transmission
- ⊙With memory, can store 100,000 ENA-13 code
- ⊙Full independent intellectual property rights
- ⊙One full charge support 100,000 times scanning



Light Source	Visible Laser Diode 650nm	Size	L × W × H:170mm × 71mm × 98mm
Scan Pattern	Single Scan & Manual	Charge Mode	Wired charging
Working Frequency	433 MHz ISM frequency	Weight	180g
Communication Distance	Up to 300m at open places	Material	ABS+PC
Scan Precision	3mil	Voltage	2200 mAh/DC 5V
Scan Rate	300 times/second	Operating Current	110mA/35mA
Scan Width	30mm@scan window,220mm@200m	EMC	CE & FCC DOC compliance
Depth of Scan Field	0-280mm(0.33mm pcs0.9)	IP Standard	IP54
Scan Angle	30° & 65° & 55°	Decoding Capability	all 1D barcode including GS1
Communication Distance	300m	Humidity	5% to 95% relative humidity
Print Contrast	10% UPC/EAN 100%	Shock	1.5M drops
Interface	USB		
Decoding Capability	UPC-A; UPC-E; EAN-8; EAN-13; Code39; Codabar; Code128; Interleaved 2 of 5; Industrial 2 of 5; Matrix 2 of 5; Code 93; UCC/EAN 128; MSI; UK/Plessey; ISBN/ISSN; GS1 Databar Expanded; GS1 Databar; GS1 Databar Limited, etc.		



**SUNLUX IOT Technology (Guangdong) Inc.**

Office Add: 4F,No.7 ,Kehui First Street ,Science Road,Science City,Guangzhou,China

Tel: +86-20-32053765 Fax: +86-20-82115390 Site: [www.xl-scan.com](http://www.xl-scan.com) E-mail: [sales@xl-scan.com](mailto:sales@xl-scan.com)