

XL-3610 2D BARCODE SCANNER



- Unique appearance, stylish shape, modern design
- 0.3 million global shutter camera, fast reading speed 60fps/s
- Fast reading on all 1D/2D barcode on paper and screen
- Quick decoding 3mil barcode and difficult barcodes
(blurred, wrinkled, low contrast, high density, high accuracy, long barcode)
- Compatible with Windows 7/8/10, iOS, Android, Linux system
- Suitable for retail stores, supermarkets, restaurant, pharmacy



THE PERFORMANCE PARAMETERS

Image Sensor	CMOS
Light Levels	White LED (Lighting) RED aiming light
CPU	32bit ARM
Exposure	Global Shutter
Image size	640x480 pixels
Scanning speed	60fps
Decoding Depth	60-360mm (13mil PCS90%)
Minimum Resolution	3mil
Interface	USB-HID, USB-VCP, RS232
Scan Mode	Manual & Automatic
Materials	ABS+TPU
Size	L*W*H : 163*68*80(mm)
Weight	185g
Input Voltage	DC 3.6V-5.5V
Working current	142mah
Stand-by current	42mah
Temperature(Operating)	-10°C — 50°C
Temperature(Storage)	-20°C — 60°C
Indicate	LED Indicator and Buzzer
Cable Standard	1.5m
Humidity	5% — 95%(non-condensing)
Light Source	0 — 5000Lux(fluorescent light), 0—100,000Lux(daylight)
Decoding Capability	1D: Codabar, Code11, Code39, Code32, Interleaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, Code93, Code128, GS1-128, UPC-A, UPC-E, EAN 8, EAN 13, GS1 DataBar, RSS14, GS1 DataBar Limited, GS1 DataBar Expanded, etc. 2D: PDF417, Micro PDF417, QR Code, Micro QR, Data Matrix, Aztec Code

SUNLUX IOT TECHNOLOGY (GUANGDONG) INC.

Office Add: 4F, No.7, Kehui First Street, Science Road, Guangzhou, China
 Tel: +86-20-32053765 Fax: +86-20-82115390
 Site: www.xl-scan.com
 E-mail: sales@xl-scan.com

